

LINK 360 L / LINK 320 L / LINK 300 L

Semirotary Letterpress Label Printing Press



► Letterpress

precise register
highest printing quality

► semirotary

the most economical
conventional printing process
for short runs

► rotary

high speed
high volume production

Features

- meets most requirements of label printing and finishing
- fast set up and few waste, job changing in 15 minutes possible
- Touch screen operation, 3 modes: semirotary, full rotary, second pass
- roller adjusting without tools
- anti-shadow roller system eliminates double image and gear marks
- quick cleaning system
- automatic lubrication system
- servo drive

unique with Link Label

- semirotary
- cold foil stamping
- semirotary
- print on glue



Grafische Systeme Volker Schischke Handelsgesellschaft mbH

Administration & Service: Nikolaus-Otto-Straße 8 • D-40670 Meerbusch

Telefon +49 (0) 2159 - 696490 • info@grafische-systeme.com

Sales: Falkenhäger Weg 34 a • D-17192 Waren

Telefon +49 (0) 3991 - 165850 • h.grundmann@grafische-systeme.com

www.grafische-systeme.com

LINK 360 L / LINK 320 L / LINK 300 L

Semirotary Letterpress Label Printing Press



Reverse Printing

- ▶ semirotary
- ▶ delam-relam



Flexo Printing

- ▶ ceramic anilox roller
- ▶ UV-Dryer



Die Cut

- ▶ rotary
- ▶ magnetic cylinder



Hot Foil

- ▶ turnable head
- allows foil feeding cross and length



Lamination



Cold Foil

- ▶ semirotary



Hot Foil

- ▶ semirotary



Selection of different rewind units
with varying performance features

Technical Data

	LINK 300 L	LINK 320 L	LINK 360 L
Unwind Ø	500 mm	700 mm	700 mm
web width min.:	50 mm	60 mm	50 mm
web width max.:	300 mm	330 mm	360 mm
printing width max.:	280 mm	310 mm	340 mm
printing lenght max.:	200 mm	250 mm	300 mm
max. mech. speed:	15.000 imp/h.	15.000 imp/h.	15.000 imp/h.
Drying	UV	UV	UV